



italtec

Company with Quality
System Certified by DNV
ISO 9001/2000

ELECTRIFICATIONS FOR LABORATORY BENCHES

The "metallic distribution modules" can be placed both over and under the worktop of the bench.

They can be also used in vertical position like supply columns.

They are supplied complete with 2 meters long power cord.

Standard dimensions: cm. 100 x 8 x 8. Special dimensions on request.

IT.0100.CA - Metallic distribution module type A

- Magneto-thermal switch 1P+N 16A with differential section 30mA
- Pilot lamp
- 4 universal sockets 220V 10/16A Italian Schuko- USA



IT.0100.CB - Metallic distribution module type B



- 8 universal sockets 220V 10/16A Italian Schuko- USA

IT.0100.CC - Metallic distribution module type C

- Magneto-thermal switch 1P+N 16A with differential section 30mA
- Emergency pushbutton
- Consent by means of key switch with contactor.
- Pilot lamp
- 4 universal sockets 220V Italian Schuko- USA



IT.0100.CD - Metallic distribution module type D



- Magneto-thermal switch 1P+N 16A with differential section 30mA
- Pilot lamp
- 4 universal sockets 220V Italian Schuko- USA
- Single-phase outputs, insulated by means of safety transformer 1x12V and 1x24V 4A, protected by means of two unipolar 4A magneto-thermal switches.

Copyright © italtec s.r.l. All Rights Reserved

Ci riserviamo di apportare modifiche e migliorie senza preavviso
We reserve the right to change these specifications without notice
Photos et données techniques susceptibles de modifications sans avis

ITALTEC S.R.L. SISTEMI TECNICI DIDATTICI
20090 FIZZONASCO MI (Italy) – Via privata Liguria, 3
Tel. +39 02-90.721.606 Fax. +39-02-90.720.227
e-mail: italtec@italtec.it <http://www.italtec.it>



italtec

Company with Quality
System Certified by DNV
ISO 9001/2000

ELECTRIFICATIONS FOR LABORATORY BENCHES

IT.0100.CF - Metallic distribution module type F

- Magneto-thermal switch 1P+N 16A with differential section 30mA
- Pilot lamp
- 4 universal sockets 220V Italian Schuko- USA
- Single-phase outputs insulated by means of safety transformer 2x12V and 2x24V 4A, protected by means of two unipolar 4A magneto-thermal switches.



IT.0100.CG - Metallic distribution module type G



- Magneto-thermal switch 1P+N 16A with differential section 30mA
- Emergency pushbutton
- Consent by means of key switch with contactor
- Pilot lamp
- 4 universal sockets 220V Italian Schuko- USA
- Single-phase outputs insulated by means of safety sockets 2x12V and 2x24V 4A, protected by means of two unipolar 4A magneto-thermal switches.

IT.0100.CAA - Metallic distribution module type H

- 10A Bipolar magneto-thermal switch
- 30mA pure differential switch
- Pilot lamp
- 4 universal sockets 220V 10/16A Italian Schuko- USA



IT.0100.CAB - Metallic distribution module type I



- 10A Bipolar magneto-thermal switch
- Prearranged for placement of 30mA pure differential switch
- Pilot lamp
- 4 universal sockets 220V 10/16A Italian Schuko- USA

Copyright © italtec s.r.l. All Rights Reserved

Ci riserviamo di apportare modifiche e migliorie senza preavviso
We reserve the right to change these specifications without notice
Photos et données techniques susceptibles de modifications sans avis

ITALTEC S.R.L. SISTEMI TECNICI DIDATTICI
20090 FIZZONASCO MI (Italy) – Via privata Liguria, 3
Tel. +39 02-90.721.606 Fax. +39-02-90.720.227
e-mail: italtec@italtec.it <http://www.italtec.it>